

partners.

Please send your enquiries to: hochwasserschutz@prefa.com

FLOOD PROTECTION SOLUTIONS INFORMATION FORM

PREFA TEMPLATE

PROJECT INFORMATION

Name:			
Street:			
Town postcode:			
Tel.:			
Fax:			
Email:			
WATER STORAGE LEVEL:	INSTALLATION		-
m		COVER	
CLEAR WIDTH:		straight 🗌 angul	ar cover none
m		Lockin	g screw for cover:
clear width			_
			no
QUANTITY: pc.			
COVER FOR GROUND SLEEVE:		ACCESSORIES	
aluminium	fitted in front of the reveal	COMPRESSI	_
stainless steel		☐ yes, with star-shaped handle	☐ yes, with hex-head screw
COATING:		with star shaped handre	with next nead below
no			933
yes			
colour:		ľ	I
☐ barrier panels (≤ 3 m)			
side parts	fitted flush in the reveal	BRACKET	
cover		(FOR STORING THE BARRIER PANELS)	
storage casing			
COMMENT:			
		☐ yes	
		∐ no	
	in the reveal	STORAGE CASING	
CAUTION:		STORAGE	OASINO -
The supporting structure for the system must be even to ensure that			
the ground seal can be optimally adapted. Furthermore, in the case of paving stones, adequate foundation work and fastening must be		∐ yes □ no	
ensured to avoid erosion.	non work and lastening must be		
Prior to installing the PREFA flood	= = = = = = = = = = = = = = = = = = = =		4
first make sure that the building is structurally suitable for mounting the system.		☐ PERMANENT GROUND SEAL	
All PREFA flood protection solutions are available from our PREFA		(this is required if the flood protection system is permanently installed)	